



# Pressure Safety Value (PSV) Blinds

Increased Safety, Decreased Environmental Impact



## EZ Guillotine® Slip Blind

EZ Guillotine slip blinds are used to provide an isolation source on the downstream side, commonly known as the flare header side, of a PSV prior to removal for repair. The EZ Guillotine is not rated to hold more than 1-2 pounds of pressure.

Customers use the EZ Guillotine blind to enhance the safety for technicians, and reduce the release of hydrocarbons or chemicals in the surrounding area while removing a PSV when the pressure in the flare header is low enough to perform this - roughly zero to one pound. Even at these low pressures, an open-ended pipe can release a large amount of vapor rapidly into the area. In this situation there is the possibility that a spark can set off the vapor cloud and start a fire. The EZ Guillotine slip blind greatly minimizes this open exposure to just seconds when installed efficiently and correctly. After removal of the PSV a blind flange is installed over the EZ Guillotine to hold everything in place against any intermittent pressure.

**AVAILABLE FOR SALE**

**4" & Larger**

**3" & Smaller**



### How did USA Industries come up with the design for the EZ Guillotine Slip Blind?

The same way many of our products are developed and come to market. A customer had a need, and they asked us to help come up with a design. As a custom machine shop, we're always looking for new, inventive solutions to our customers' every day problems. Got a problem of your own? Reach out and let us know!

*Available in Carbon and Stainless Steels or Other Alloys to Meet Your Specifications!*

#### When Ordering Specify:

- Line Size
- Flange Rating
- Thickness
- Material
- Color Coded Handle
- Quantity
- Delivery Date

FLANGE RATING / COLOR CODED HANDLE COLORS	
150#	RED
300#	BLUE
600#	YELLOW
900#	GREEN
1500#	WHITE
2500#	ORANGE

For more information on USA Industries products, contact us at (713) 941-3797 or go to [www.USAINdustries.com](http://www.USAINdustries.com)